

SUGGESTED HYDRAULIC FLUIDS FOR MULTIPRESS EQUIPMENT

DEFINITION OF FLUID TERMS

- **LUBRICITY** - The ability of oil to keep friction low between moving parts.
- **VISCOSITY** - The thickness of oil or the resistance to flow.
- **VISCOSITY INDEX** - The measurement of the rate which the viscosity of oil changes with temperature (the higher the VI index, the more stable the viscosity is as the temperature changes).
- **RUST INHIBITOR** - Prevents the effects of condensation in oil, and helps to retain oil on the surface, therefore it retards rusting.

The following oils have a viscosity of 300 or more at 100°F, a SUS Rating of 53 or better @ 210°F, an ISO Grade of 68 or better, and Viscosity Index of 94 or better, and contain the following additives: Anti Foam, Anti Wear, and Anti Rust.

COMPANY	BRAND NAME	MFG. GRADE
American Oil Co.	Rykon	68
AMSOIL (Synthetic)	RCJ	68
AMSOIL (Synthetic)	ATH AWS	68
Atlantic Richfield	Duro AW	S-315
Ashland/Valvoline		AW 30
BP Oil	Energol	68
Castrol	Hyspin AWH	68
	Hyspin AW 5	68
Chevron	Chevron EP	68
Cities Service	Citgo AW	68
	Citgo Pacemaker	68
Conoco	GP DEXTOL R & O	33
Cooks	Albavis	20
DA Lubricant	DA Hydro Power	68
Exxon	Nuto H	68
	Nuto	68
Fiske	Lubriplate	HO-2
Gulf	Security	68 AW
	Harmony	68
Kendall	Kenoil R & O	68
Mobil Oil	DTE 10 Series	16
	DTE 20 Series	26
	DTE	Med Heavy
Pacer Lubricants	Pacer Power	V68

~~10~~

~~10/10~~

COMPANY	BRAND NAME	MFG. GRADE
Penzoil	AW Hyd Oil	68
Shell	Tellus	68
Sun Oil	Sunvis	754
	Sunvis WR	831
	Suntac WR	302 WR
Texaco	Rando	HD 68
Union Oil	Unax AW	315
	Spec Hydraulic	315

The following list is for AGMA #8 oil or equivalent, suitable for *MULTIPRESS* 100 or 300 Series Index Tables.*

INDEX TABLES

COMPANY	BRAND NAME	MFG. GRADE
American	PQ Gear Lube	AGMA8EP
AMSOIL (Synthetic)	SGO	150 460
Ashland/Valvoline	EP Compound	200
BP Oil	Extra Duty Gear Oil	140
Cities Service	EP Compound	150
Cooks	EP Gear Lube	140
Exxon	Spartan	EP680
	PENOLED	EP6
Fiske	Lubriplate #8	APG 140
Grainers	AGMA 8 Oil	ZW577
Gulf	EP Lube	S 180
Mobil	Mobil Gear	634
	Mobil Gear	636
Shell	OMALA	460
	OMALA	680
Sun	Sun EP	1130
	Sun EP	1150
Texaco	Meropa	680
Chevy Dealers	Posi-Traction Rear End Oil	

* Note that gear oil is to be mixed with hydraulic fluid for index table use. See instruction booklet.

The above list by no means is a complete listing of all manufacturers and their products supplied to our customers. However, this list is to be used as a guide to recommend oils to be used in our products.

